## **CERTIFICATE OF CONFORMITY**

This Certificate of Conformity is hereby issued to the product designated below:

Certificate No.....: 22EP02024T01

Report No.....: EP2202024T01

Date Issue. ....: 2022-04-18

Applicant's name ...... XingYuan Electronics Co.,Ltd

Address .....: 227 of Xiasha Road, Shipai Town,523350 Dongguan City, Guangdong

Province, People's Republic of China

Manufacturer's name ......: Same as applicant

Address .....: Same as applicant

Product Description.....: LED DRIVER

Model(s)/Type References: XY24LI-xxxyyyVQ-ZW (xxx and yyy are variables, see appendix for

details)

Parameters.....: Input: 100-240V~, 50/60Hz, 0.5A Max

Output: 5.0-30.0Vdc, 0.01-3.0A, 24.0W Max

**Standard(s)** .....: AS CISPR15:2017

The device bearing the trade name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified. (Refer to Test Report if any modifications were made for compliance)

This certificate of conformity is based on a single evaluation of the submitted sample(s) of the above mentioned product. It does not imply an assessment of the whole production have to be observed.

Approved By

Eric Liu

Director of engineering department

Dongguan Pubiao Testing Technology Co., Ltd

No. 3, First Floor, Building A, No.30, Minghua Road, Juzhou village, Shijie Town, Dongguan City Guangdong China Tel: +86 769 81813516 E-mail: service@pubiaotest.com Web: www.pubiaotest.com

## **CERTIFICATE OF CONFORMITY**

Appendix of Certificate No.: 22EP02024T01

## Table A: Definition of variables

Variable	Range of variable	Content		
xxx	050-300	3 digits, indicates 10 times of output voltage in V and in step of 0.1V. eg. 050=5.0V, 300=30.0V.		
ууу	00 <sup>1</sup> -300	3 digits, indicates 10 times of output current in A and in step of 0.01A. eg. 001=0.01A, 300=3.0A.		

## Table B: Model list and output rating

Model	Output voltage (Vdc)	Output current (A)	Max Power (W)	Transformer
	5.0-6.0V	0.01-3.0	18.00	XY24LI-050300V-T1
XY24LI-xxxyyyVQ-ZW	9.0-17.0	0.01-2.6	24.00	XY24LI-120200V-T1
	17.1-30.0	0.01-1.4	24.00	XY24LI-240100V-T1