

TÜV SÜD  
ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT



Product Service

# Attestation of Conformity

No. N8A 079435 0308 Rev. 00

**Holder of Certificate:** **XING YUAN ELECTRONICS CO., LTD**  
No. 227 of Xiasha Road, Shipai Town  
523350 Dongguan City, Guangdong Province  
PEOPLE'S REPUBLIC OF CHINA

**Product:** **Power supplies  
(LED DRIVER)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

**Test report no.:** 651401901801

**Date,** 2019-04-29

( Taylor Yao )

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

TÜV®



Product Service

# Attestation of Conformity

No. N8A 079435 0308 Rev. 00

**Model(s):** XY36J-xxxxyyVH-EW; XY36J-xxxxyy0H-EW;  
 XY36J-xxxxyyVH-BW; XY36J-xxxxyyVH-BT  
 ('xxx'=120-240 indicates rated output voltage  
 ( $U_{rated}$ ) 12.0-24.0VDC, in steps of 0.1VDC;  
 'yyy'=010-300 indicates output current 0.10-3.00A,  
 in steps of 0.01A)

**Brand:** XY



## Parameters:

Rated Input Voltage : 220-240VAC  
 Rated Frequency : 50/60Hz  
 Rated Input Current : 0.5A Max.  
 Rated Output : See below table for details  
 Protection against Electric Shock : Class II; SELV  
 Degree of Protection : IP20  
 Method of Installation : Independent  
 Type of Output : Constant voltage type  
 $t_a$  : 40°C  
 $t_c$  : 75°C

Model	$U_{rated}$ (VDC)	Output Current (A)	$P_{rated}$ (W) Max.
XY36J-xxxxyyVH-EW, XY36J-xxxxyy0H-EW, XY36J-xxxxyyVH-BW, XY36J-xxxxyyVH-BT	12.0-18.0	0.10-3.00	36.0
	18.1-24.0	0.10-1.50	36.0

**Tested according to:** EN 61347-1:2015  
 EN 61347-2-13:2014/A1:2017  
 EN 62493:2015