

# ATTESTATION OF CONFORMITY

Issued to: XY POWER SUPPLY LIMITED  
Baodong Road, ShaoYang Economic Development Zone, ShaoYang City, HuNan Province, China

For the product: LED driver



Trade name:

Type/Model: see annex.

Ratings: ta: 40 °C, tc: 75 °C, Safety isolating non-inherently shorted circuit proof, Class II, independent;  
Input: 220-240 Vac, 50/60 Hz, 0,4 A Max.;  
Other ratings see "General product information" of test report for details

Manufactured by: XING YUAN ELECTRONICS CO., LTD  
No. 227 of Xiasha Road, Shipai Town, 523350 Dongguan City, Guangdong Province, CHINA

Requirements: EN 61347-1:2015 + A1:2021  
EN 61347-2-13:2014 + A1:2017  
EN 62493:2015

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no 4900023.50.

This Attestation implies that the examined types are in accordance with the standards designated under the Low Voltage Directive (LVD) 2014/35/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

The CE marking may be affixed on the product if all relevant and effective EC directives are complied with.

Arnhem, 15 May 2023  
DEKRA Testing and Certification (Shanghai) Ltd.,  
Guangzhou Branch

Number: 4900023.01AOC

A handwritten signature in blue ink, appearing to read 'Rosa Zhou'.

Rosa Zhou  
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed



# Annex

Document no. : 4900023.01AOC

Model list:

Model	Output Voltage (Vdc)	Output current (A)	Power Max (W)	Transformer	Circuit and PCB layout
XY24LR-xxxxyyVH-EW, XY24LR-xxxxyyVH-BW, XY24LR-xxxxyyVH-ET, XY24LR-xxxxyyVH-BT, XY24LQ-xxxxyyVH-EW	5,0-6,0	0,1-3,0	18	XY24LR-050300V-T1	same
	9,0-17,0	0,1-2,5	24	XY24LR-120200V-T1	
	17,1-30,0	0,1-1,4	24	XY24LR-240100V-T1	
<p>Note:</p> <ol style="list-style-type: none"> <li>“xxx” = 050-300 indicates rated output voltage range 5,0-30,0 Vdc; For example, 050 = 5,0 Vdc, 300 = 30,0 Vdc, the rated output voltage is rising in step of 0,1 Vdc;</li> <li>“yyy” = 001-300 indicates the rated output current range 0,1-3,0 A; For example, 010 = 0,1 A, 300 = 3,0 A, the rated output current is rising in step of 0,01 A.</li> </ol>					

End